




64G5 6U VME Multifunction I/O Boards

6U VME Multifunction I/O Board

The 64G5 is NAI's rugged 6U VME multifunction I/O and communications board. It provides low power/high-performance I/O capabilities specifically designed for demanding aerospace, defense, and industrial applications. The board can accommodate up to six NAI Configurable Open Systems Architecture™ (COSA®) smart function modules. By configuring the 64G5 with these modules, engineers can tailor the board's functionality for specific application needs, accelerating the deployment of SWaP-C optimized systems.



Features

- COSA® Architecture
- 100+ modules to choose from
- Up to 6 independent smart I/O function modules supported
- Independent x1 SerDes interface to each function module slot
- Front and/or rear I/O
- 2x 10/100/1000 Base-T Ethernet; 2 to rear or 1 to rear and 1 to front I/O
- Continuous Background Built-in-Test (BIT)
- Intelligent I/O library support included
- VICTORY Interface Services (Contact factory)
- Commercial or rugged applications
- Operating temp: 0° C to +70° C or Rugged -40° C to +85° C

Select up to 6 independent functions for your application

| I/O Modules | | | | | |
|--------------------------------------|------------|--|---|---------------------------|---|
| Function | Module | Description | Function | Module | Description |
| Analog-to-Digital | <u>AD1</u> | 12 CH. A/D, ± 10 V, Dedicated, 256 kHz (max), Sigma-Delta | Digital IO - Differential Transceiver | <u>DF1</u> | 16 CH. Differential I/O, Input: -10 V to +10 V (422), -7 V to +12 V (485) Output: -25 V to +5 V |
| | <u>AD2</u> | 12 CH. A/D, ± 100 V (max), Dedicated, 256 kHz (max), Sigma-Delta | | <u>DF2</u> | 16 CH. 16 Channel Enhanced Differential I/O |
| | <u>AD3</u> | 12 CH. A/D, ± 25 mA, Dedicated, 256 kHz (max), Sigma-Delta | Discrete IO - Multichannel, Programmable | <u>DT1</u> | 24 CH. Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out) |
| | <u>AD4</u> | 16 CH. A/D, ± 10 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR | | <u>DT2</u> | 16 CH. Discrete I/O, ± 80 V Input/Output, Max Iout 600 mA, Isolated/Ch Switch (out) |
| | <u>AD5</u> | 16 CH. A/D, ± 50 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR | | <u>DT3</u> | 4 CH. Discrete Hi & Lo Side Switch Output @ 65V/2A (max), external individual supplied VCC & VSS per channel pair |
| | <u>AD6</u> | 16 CH. A/D, ± 100 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR | | <u>DT4</u> | 24 CH. Enhanced DT1 |
| | <u>ADE</u> | 16 CH. A/D, ± 10 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling | | <u>DT5</u> | 16 CH. Enhanced DT2 |
| | <u>ADF</u> | 16 CH. A/D, ± 100 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling | Relay | <u>RY1</u> | 4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Non Latching |
| Digital-to-Analog | <u>DA1</u> | 12 CH. D/A, ± 10 V, 25 mA Per Channel, Current or Voltage Control | | <u>RY2</u> | 4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Latching |
| | <u>DA2</u> | 16 CH. D/A, ± 10 V, 10 mA Per Channel, No Current Control | Digital IO - TTL, CMOS | <u>TL1</u> | 24 CH. TTL I/O, Standard Functionality, Programmable |
| | <u>DA3</u> | 4 CH. D/A, ± 40 V, ± 100 mA, Voltage or Current Output | | <u>TL2</u> | 24 CH. TTL I/O, Enhanced Functionality, Programmable |
| | <u>DA4</u> | 4 CH. D/A, ± 20 to ± 80 , 10 mA, Voltage Control Only | Variable Reluctance | <u>VR1</u> | 8 CH. Variable Reluctance Signal Input and General-Purpose Pulse Counter, ± 100 V, 100 kHz (max) |
| | <u>DA5</u> | 4 CH. D/A, High-Voltage/High-Current Half-Bridge (2 Channels Full-Bridge) External VCC Sourced Outputs | | | |
| Measurement & Simulation Modules | | | | | |
| Function | Module | Description | Function | Module | Description |
| AC Reference | <u>AC2</u> | 2 CH. AC Reference Source, 47 Hz - 20 KHz, $\pm 3\%$ Acc, 2 - 28 Vrms, 6 VA (Max/Ch) Power | LVDT RVDT Measurement and Simulation | <u>LD5</u> | 4 CH. LVDT/RVDT to Digital, 28-90 Vrms Input, 2-115 Vrms Exc, 47 Hz - 1 KHz Freq |
| | <u>AC3</u> | 2 CH. AC Reference Source, 47 Hz - 2.5 KHz, $\pm 3\%$ Acc, 28 - 115 Vrms, 6 VA (Max/Ch) Power | | <u>DSx</u> (<u>DRx</u>) | 1 - 3 CH. Digital to Synchro/Resolver, 2 - 90 VLL, 2 - 1115 Vrms Exc, 47 Hz - 20 kHz Freq |
| LVDT RVDT Measurement and Simulation | <u>DLx</u> | 1 - 3 CH. Digital to LVDT/RVDT, 2 - 90 Vrms Full Scale, 2 - 115 Vrms Exc, 47 Hz - 20 kHz Freq | Synchro Resolver Measurement and Simulation | <u>SDx</u> | 4 CH. Synchro/Resolver to Digital, 2 - 90 Vrms Input, 2 - 115 Vrms Exc, 47 Hz to 20 kHz Freq |
| | <u>LD1</u> | 4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 47 Hz -1 KHz Freq | | <u>RT1</u> | 8 CH. Resistance Temperature Detectors (RTD), 2, 3, or 4 wire, 16 Bit Res, 16.7 Hz/Ch |
| | <u>LD2</u> | 4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 1 KHz - 5 KHz Freq | Thermocouple and RTD Measurement | <u>TC1</u> | 8 CH. Thermocouple, 4.17 - 470 Hz, ± 100 mV A/D |
| | <u>LD3</u> | 4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 5 KHz - 10 KHz Freq | | <u>TR1</u> | 8 CH. Thermocouple (TCx) & Resistance Temperature Detectors (RTD), programmable per channel |
| | <u>LD4</u> | 4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 10 KHz - 20 KHz Freq | Strain Gauge Measurement | <u>SG1</u> | 4 CH. Strain Gauge, 4.7 Hz - 4.8 KHz, Measurement, Conventional 4-Arm Bridge |

| Communication Modules | | | | | |
|------------------------------|------------|--|-----------------------|------------|---|
| Function | Module | Description | Function | Module | Description |
| ARINC Communications | <u>AR1</u> | 12 CH. ARINC 429, 100 KHz or 12.5 KHz, RX/TX, 256 Word Tx/Rx Buffer | MIL-STD-1553B | <u>FTE</u> | 2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled |
| | <u>AR2</u> | 1 CH. ARINC 568 (CH-1, RX & TX) & 1 Channel ARINC 579 (CH-2, Programmable RX or TX), 1024-Word TX & RX Buffers per Ch. | | <u>FTF</u> | 4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled |
| CANBus Communications | <u>CB1</u> | 8 CH. CANBus, CAN 2.0 A/B, 16 K RX/TX Buffer, 1 Mb/s Max Data Rate | MIL-STD-1760 | <u>FTJ</u> | 1 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled |
| | <u>CB2</u> | 8 CH. CANBus, J1939, 16 K RX/TX Buffer, 500 kb/s Max Data Rate | | <u>FTK</u> | 2 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled |
| | <u>CB3</u> | 8 CH. CANBus, CAN 2.0 A/B (CB1) or J1939 (CB2) protocol layer programmable per channel | Serial Communications | <u>SC1</u> | 4 CH. Serial, RS-232/422/423 (MIL-STD-188C)/485, Non Isolated |
| MIL-STD-1553B | <u>FTA</u> | 1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled | | <u>SC3</u> | 8 CH. (max) RS-232/422/485 Serial Communications or GPIO, Programmable, Non-isolated |
| | <u>FTB</u> | 2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled | | <u>SC5</u> | 4 CH. RS-232/422/485 communications, isolated per channel and from SYS GND |
| | <u>FTC</u> | 4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled | | <u>SC6</u> | 4 CH. RS-232/422/485 communications, individual SYS GND provided per channel (non-isolated) |
| | <u>FTD</u> | 1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Direct Coupled | | | |
| Storage | | | | | |
| Function | Module | Description | Function | Module | Description |
| SATA Solid State Drive (SSD) | <u>FM2</u> | 1 CH. 480 GB MLC SATA Flash, extended temp -40°C to 85°C operation | | | |
| Combination Modules | | | | | |
| Function | Module | Description | Function | Module | Description |
| Combo | <u>CM5</u> | 2 CH. Dual-redundant MIL-STD-1553 & 8 Channel ARINC 429/575, 100 KHz or 12.5 KHz, RX or TX, 256 Word Tx/Rx Buffer | | | |

Architected for Versatility

NAI's Configurable Open Systems Architecture™ (COSA®) offers a choice of over 100 smart I/O, communications, or Ethernet switch functions, providing the highest packaging density and greatest flexibility of ruggedized embedded product solutions in the industry. Preexisting, fully-tested functions can be combined in an unlimited number of ways quickly and easily.

One-Source Efficiencies

Eliminate man-months of integration with a configured, field-proven system from NAI. Specification to deployment is a seamless experience as all design, state-of-the-art manufacturing, assembly and test are performed - by one trusted source. All facilities are located within the U.S. and optimized for high-mix/low volume production runs and extended lifecycle support.

Product Lifecycle Management

From design to production and beyond, NAI's product lifecycle management strategy ensures the long-term availability of COTS products through configuration management, technology refresh and obsolescence component purchase and storage.

All specifications are subject to change without notice. All product and company names are trademarks or registered trademarks of their respective holders

