





75G5 3U cPCI Multifunction I/O Boards

3U cPCI Multifunction I/O Board

The 75G5 is NAI's rugged 3U cPCI multifunction I/O and communications board. It provides low power/high-performance I/O capabilities specifically designed for demanding aerospace, defense, and industrial applications. The board can accommodate up to three NAI Configurable Open Systems Architecture™ (COSA®) smart function modules. By configuring the 75G5 with these modules, engineers can tailor the board's functionality for specific application needs, accelerating the deployment of SWaP-C optimized systems.



Features

- Up to 3 independent smart I/O function modules supported
- Front and/or rear I/O
- Commercial or rugged applications
- < 5 W MB power dissipation
- Independent x1 SerDes interface to each function module slot
- 2x 10/100/1000 Base-T Ethernet; 2 to rear or 1 to rear and 1 to front I/O
- Continuous Background Built-in-Test (BIT)
- Intelligent I/O library support included
- COSA® Architecture
- VICTORY Interface Services (Contact factory)
- Operating temp: 0° C to +70° C or Rugged -40° C to +85° C

Select up to 3 independent functions for your application

I/O Modules					
Function	Module	Description	Function	Module	Description
Analog-to-Digital	<u>AD1</u>	12 CH. A/D, ± 10 V, Dedicated, 256 kHz (max), Sigma-Delta	Digital-to-Analog	<u>DA5</u>	4 CH. D/A, High-Voltage/High-Current Half-Bridge (2 Channels Full-Bridge) External VCC Sourced Outputs
	<u>AD2</u>	12 CH. A/D, ± 100 V (max), Dedicated, 256 kHz (max), Sigma-Delta	Digital IO - Differential Transceiver	<u>DF1</u>	16 CH. Differential I/O, Input: -10 V to +10 V (422), -7 V to +12 V (485) Output: -25 V to +5 V
	<u>AD3</u>	12 CH. A/D, ± 25 mA, Dedicated, 256 kHz (max), Sigma-Delta		<u>DF2</u>	16 CH. 16 Channel Enhanced Differential I/O
	<u>AD4</u>	16 CH. A/D, ± 10 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR	Discrete IO - Multichannel, Programmable	<u>DT1</u>	24 CH. Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out)
	<u>AD5</u>	16 CH. A/D, ± 50 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR		<u>DT2</u>	16 CH. Discrete I/O, ± 80 V Input/Output, Max Iout 600 mA, Isolated/Ch Switch (out)
	<u>AD6</u>	16 CH. A/D, ± 100 V, Multiplexed, 500 KHz Agg / 8 Ch, SAR		<u>DT3</u>	4 CH. Discrete Hi & Lo Side Switch Output @ 65V/2A (max), external individual supplied VCC & VSS per channel pair
	<u>ADE</u>	16 CH. A/D, ± 10 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling		<u>DT4</u>	24 CH. Enhanced DT1
	<u>ADF</u>	16 CH. A/D, ± 100 V, Individual 16-bit SAR, 200 kHz max., Simultaneous Sampling		<u>DT5</u>	16 CH. Enhanced DT2
Chip Detector and Fuzz Burn	<u>CD1</u>	6 CH. Chip Detector (CD) and Fuzz Burn (FB)	Relay	<u>RY1</u>	4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Non Latching
Digital-to-Analog	<u>DA1</u>	12 CH. D/A, ± 10 V, 25 mA Per Channel, Current or Voltage Control		<u>RY2</u>	4 CH. Relay, 220V/2A @ 60W/62.5VA (Max), Latching
	<u>DA2</u>	16 CH. D/A, ± 10 V, 10 mA Per Channel, No Current Control	Digital IO - TTL, CMOS	<u>TL1</u>	24 CH. TTL I/O, Standard Functionality, Programmable
	<u>DA3</u>	4 CH. D/A, ± 40 V, ± 100 mA, Voltage or Current Output		<u>TL2</u>	24 CH. TTL I/O, Enhanced Functionality, Programmable
	<u>DA4</u>	4 CH. D/A, ± 20 to ± 80 , 10 mA, Voltage Control Only	Variable Reluctance	<u>VR1</u>	8 CH. Variable Reluctance Signal Input and General-Purpose Pulse Counter, ± 100 V, 100 kHz (max)
Measurement & Simulation Modules					
Function	Module	Description	Function	Module	Description
AC Reference	<u>AC2</u>	2 CH. AC Reference Source, 47 Hz - 20 KHz, $\pm 3\%$ Acc, 2 - 28 Vrms, 6 VA (Max/Ch) Power	Synchro Resolver Measurement and Simulation	<u>DSx (DRx)</u>	1 - 3 CH. Digital to Synchro/Resolver, 2 - 90 VLL, 2 - 1115 Vrms Exc, 47 Hz - 20 kHz Freq
	<u>AC3</u>	2 CH. AC Reference Source, 47 Hz - 2.5 KHz, $\pm 3\%$ Acc, 28 - 115 Vrms, 6 VA (Max/Ch) Power		<u>SDx</u>	4 CH. Synchro/Resolver to Digital, 2 - 90 Vrms Input, 2 - 115 Vrms Exc, 47 Hz to 20 kHz Freq
LVDT RVDT Measurement and Simulation	<u>DLx</u>	1 - 3 CH. Digital to LVDT/RVDT, 2 - 90 Vrms Full Scale, 2 - 115 Vrms Exc, 47 Hz - 20 kHz Freq	IRIG Timecode Receiver and Generator	<u>RG1</u>	1 CH. IRIG Timing Function Interface
	<u>LD1</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 47 Hz - 1 KHz Freq	Thermocouple and RTD Measurement	<u>RT1</u>	8 CH. Resistance Temperature Detectors (RTD), 2, 3, or 4 wire, 16 Bit Res, 16.7 Hz/Ch
	<u>LD2</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 1 KHz - 5 KHz Freq		<u>TC1</u>	8 CH. Thermocouple, 4.17 - 470 Hz, ± 100 mV A/D
	<u>LD3</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 5 KHz - 10 KHz Freq		<u>TR1</u>	8 CH. Thermocouple (TCx) & Resistance Temperature Detectors (RTD), programmable per channel
	<u>LD4</u>	4 CH. LVDT/RVDT to Digital, 2-28 Vrms Input, 2-115 Vrms Exc, 10 KHz - 20 KHz Freq	Strain Gauge Measurement	<u>SG1</u>	4 CH. Strain Gauge, 4.7 Hz - 4.8 KHz, Measurement, Conventional 4-Arm Bridge
	<u>LD5</u>	4 CH. LVDT/RVDT to Digital, 28-90 Vrms Input, 2-115 Vrms Exc, 47 Hz - 1 KHz Freq			

Communication Modules					
Function	Module	Description	Function	Module	Description
ARINC Communications	<u>AR1</u>	12 CH. ARINC 429, 100 KHz or 12.5 KHz, RX/TX, 256 Word Tx/Rx Buffer	MIL-STD-1553B	<u>FTE</u>	2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled
	<u>AR2</u>	1 CH. ARINC 568 (CH-1, RX & TX) & 1 Channel ARINC 579 (CH-2, Programmable RX or TX), 1024-Word TX & RX Buffers per Ch.		<u>FTF</u>	4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Direct Coupled
CANBus Communications	<u>CB1</u>	8 CH. CANBus, CAN 2.0 A/B, 16 K RX/TX Buffer, 1 Mb/s Max Data Rate	MIL-STD-1760	<u>FTJ</u>	1 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled
	<u>CB2</u>	8 CH. CANBus, J1939, 16 K RX/TX Buffer, 500 kb/s Max Data Rate		<u>FTK</u>	2 CH. MIL-STD-1760 (1553), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled
	<u>CB3</u>	8 CH. CANBus, CAN 2.0 A/B (CB1) or J1939 (CB2) protocol layer programmable per channel	Serial Communications	<u>SC1</u>	4 CH. Serial, RS-232/422/423 (MIL-STD-188C)/485, Non Isolated
MIL-STD-1553B	<u>FTA</u>	1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Transformer Coupled		<u>SC3</u>	8 CH. (max) RS-232/422/485 Serial Communications or GPIO, Programmable, Non-isolated
	<u>FTB</u>	2 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled		<u>SC5</u>	4 CH. RS-232/422/485 communications, isolated per channel and from SYS GND
	<u>FTC</u>	4 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM Per Channel, Transformer Coupled		<u>SC6</u>	4 CH. RS-232/422/485 communications, individual SYS GND provided per channel (non-isolated)
	<u>FTD</u>	1 CH. MIL-STD-1553 (AMC), BC, RT, BM, BM/RT, 128 KB RAM, Direct Coupled			
Storage					
Function	Module	Description	Function	Module	Description
SATA Solid State Drive (SSD)	<u>FM2</u>	1 CH. 480 GB MLC SATA Flash, extended temp -40°C to 85°C operation			
Combination Modules					
Function	Module	Description	Function	Module	Description
Combo	<u>CM5</u>	2 CH. Dual-redundant MIL-STD-1553 & 8 Channel ARINC 429/575, 100 KHz or 12.5 KHz, RX or TX, 256 Word Tx/Rx Buffer	Combo	<u>CM8</u>	2 CH. Dual-redundant MIL-STD-1553 & 12 Channel Discrete I/O, 0-60 VDC Input/Output, Max Iout 500 mA - 2 A, Source/Sink (out)

Architected for Versatility

NAI's Configurable Open Systems Architecture™ (COSA®) offers a choice of over 100 smart I/O, communications, or Ethernet switch functions, providing the highest packaging density and greatest flexibility of ruggedized embedded product solutions in the industry. Preexisting, fully-tested functions can be combined in an unlimited number of ways quickly and easily.

One-Source Efficiencies

Eliminate man-months of integration with a configured, field-proven system from NAI. Specification to deployment is a seamless experience as all design, state-of-the-art manufacturing, assembly and test are performed - by one trusted source. All facilities are located within the U.S. and optimized for high-mix/low volume production runs and extended lifecycle support.

Product Lifecycle Management

From design to production and beyond, NAI's product lifecycle management strategy ensures the long-term availability of COTS products through configuration management, technology refresh and obsolescence component purchase and storage.

All specifications are subject to change without notice. All product and company names are trademarks or registered trademarks of their respective holders

